







PERFORMANCE SPECIFICATIONS



Condenser Dimensions:

34.0" x 18.9" x 8.4" (864 x 480 x 214 mm)



Evaporator Dimensions:

33.6" x 23.9" x 6.8" (853 x 608 x 172 mm)

Cab Command™ Dimensions:

3.4" x 2.4" x 1.1" (85 x 60 x 28 mm)



Cooling/Temperature Capacity: Ambient at 100°F (38°C) Compressor Speed: 2,400 rpm

Evaporator Return Air Temp.	Road Operation	
	BTU/hr	Watts
35°F (2°C)	7,200	2,110
0°F (-18°C)	4,700	1,380

Standard Features Include:

EasyReach™ condenser Durable composite skin Extra-flat SlimLine[™] evaporator 8 CID (131 cc) six-cylinder swash plate compressor Double-A groove clutch Refrigerant - R-404A Hot gas defrost Hot gas heating Condenser valve enhanced heating circuit Refrigerant injector Roofmount installation kit Low refrigerant pressure protection High refrigerant pressure protection Microprocessor control system

Red light visual warning (in cab)
Main On/Off system power keys
Timed defrost interval
Manual defrost key
Diagnostic safety indicators
Frozen range lockout

Cab Command™ controller

Digital readout

Cab Command (in cab)
Adjustable display brightness
Current and stored alarms
Automatic defrost control
Programmable defrost timer
Automatic defrost termination
Manual defrost override
Installation package

Refrigerant discharge muffler SureTight™ refrigerant hoses SureTight hose clamps

Accessories and Options:

Poly-V groove clutch Variable groove clutch Rear port adapter

Approximate Weights:

Condenser Weight: 66 lb (30 kg) Evaporator Weight: 37 lb (17 kg)

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-11019.

This warranty is applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-10868 Rev E.

North America Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA Central America and Mexico Carrier Transicold Ejercito Nacional 253-A Piso 5 Colonia Anahuac 11320 Mexico D.F.

