



**EXTRAORDINARY PERFORMANCE,
EXCEPTIONAL RELIABILITY,
EXCELLENT VALUE.**



Condenser Dimensions:

53.8" x 20.2" x 19.6"
(1,367 x 514 x 498 mm)



Evaporator Dimensions:

61.3" x 24.2" x 7.6"
(1,556 x 614 x 194 mm)

Cab Command™ 2 Dimensions:

3.4" x 2.4" x 1.1"
(85 x 60 x 28 mm)



Cooling/Temperature Capacity:
Ambient at 100°F (38°C)
Compressor Speed: 2,400 rpm @ 60 Hertz

Evaporator Return Air Temp.	Road BTU/hr (Watts)	Standby BTU/hr (Watts)
35°F (2°C)	17,000 (4,985)	13,000 (3,810)
0°F (-18°C)	9,000 (2,640)	6,100 (1,790)
-20°F (-29°C)	5,000 (1,465)	3,000 (880)

Standard Features Include:

- Durable DuraShell™ composite skin
- Extra-flat SlimLINE™ evaporator
- 9.8 CID (161 cc) six-cylinder swash plate compressor
- Refrigerant — R-404A
- Brushless evaporator fan motors
- Hot gas defrost
- Hot gas heating
- Condenser valve enhanced heating circuit
- Refrigerant injector
- Integrated oil separator
- Low refrigerant pressure protection
- High refrigerant pressure protection
- Microprocessor control system
 - Cab Command™ 2 (in cab) control center
 - Red light visual warning (in cab)
 - Main On/Off system power keys
 - Timed defrost interval
 - Manual defrost key
 - Diagnostic safety indicators
 - Adjustable minimum and maximum setpoint configurations
- Digital readout
 - Adjustable display brightness
 - Operation hourmeters
 - Current and stored alarms
- Automatic defrost control
 - Programmable defrost timer
 - Automatic defrost termination
 - Manual defrost override
- Installation package
 - SureTight™ refrigerant hoses
 - SureTight hose clamps

Accessories and Options:

- 208/230v/3ph/60Hz electric standby
- 208/230v/1ph/60Hz electric standby
- Poly-V groove clutch
- Variable groove clutch
- Double-A groove clutch
- Rear port adapter
- 6.8 CID (111cc) compressor (electric standby models only)

Approximate Weights:

- Condenser Weights:
 - 191 lb (87 kg) engine operation only
 - 337 lb (153 kg) with electric standby
- Evaporator Weight:
 - 92 lb (42 kg)

Specifications are subject to change without notice.
Warranty: Product warranty and limitations are outlined in Form 62-11019.
This warranty is applicable only in North America. Consult your Carrier Transcold representative for warranty coverage elsewhere. Form 62-11049 Rev F.

North America
Carrier Transcold
700 Olympic Drive
Athens, GA 30601 USA

Central America and Mexico
Carrier Transcold
Ejercito Nacional 253-A Piso 5
Colonia Anahuac
11320 Mexico D.F.

